

DRUM MANUFACTURER CROSS-REFERENCE CHART FOR HOODS*

WIRE MANUFACTURER	PACKAGING	DRUM DIA
AIR LIQUIDE®	500 LB (227 KG)	20.4" (518mm)
	900 LB (408 KG)	23.4" (594mm)
ALCO TEC WIRE®	311 LB (141 KG)	WWOC
ARCOS ALLOYS®	250 LB (113 KG)	20.4" (518mm)
	500 LB (227 KG)	20.4" (518mm)
AVESTA®	250 LB (113 KG)	20.4" (518mm)
	550 LB (250 KG)	20.4" (518mm)
	600 LB (272 KG)	20.4" (518mm)
	750 LB (340 KG)	26.0" (660mm)
	550 LB (250 KG)	20.4" (518mm)
BÖHLER®	550 LB (250 KG)	20.4" (518mm)
EAGLE®	500 LB (227 KG)	20.4" (518mm)
ESAB®	500 LB (227 KG)	20.4" (518mm)
	550 LB (250 KG)	20.4" (518mm)
	900 LB (408 KG)	23.4" (594mm)
	Octagon 500 LB (227 KG)	20.5" (521mm)
	Octagon 600 LB (272 KG)	20.5" (521mm)
GEDIK® (GeKa®)	110 LB (50 KG)	20.4" (518mm)
	485 LB (220 KG)	20.4" (518mm)
	550 LB (250 KG)	23.4" (594mm)
GRYTGOLS BRUK®	500 LB (227 KG)	20.4" (518mm)
	1000 LB (453 KG)	26.0" (660mm)
HARRIS WELCO®	500 LB (227 KG)	20.4" (518mm)
HYUNDAI®	less than 600 LB (272 KG)	20.4" (518mm)
	600 LB (272 KG)+	26.0" (660mm)
HOBART®	250 LB (113 KG)	23.4" (594mm)
	400 LB (181 KG)	20.4" (518mm)
	Tubular 500 LB (227 KG)	23.4" (594mm)
	Solid 600 LB (272 KG)	20.4" (518mm)
	Tubular 600 LB (272 KG)	23.4" (594mm)
	Tubular 700 LB (318 KG)	23.4" (594mm)
	Solid 950 LB (431 KG)	23.4" (594mm)
	Dodecagon 300 LB (136 KG)	23.4" (594mm)
	Dodecagon 100 LB (45.4 KG)	23.4" (594mm)
INE	440 LB (200 KG)	20.4" (518mm)
	550 LB (250 KG)	20.4" (518mm)
	1325 LB (600 KG)	26.0" (660mm)
ISAF	661 LB (300 KG)	20.4" (518mm)
KAYNAK®	550 LB (250 KG)	20.4" (518mm)
KOBELCO®	440 LB (200 KG)	20.4" (518mm)
	550 LB (250 KG)	20.4" (518mm)

WIRE MANUFACTURER	PACKAGING	DRUM DIA
LINCOLN ELECTRIC®	500 LB (227 KG)	20.4" (518mm)
	600 LB (272 KG)	23.4" (594mm)
	900 LB (408 KG)	23.4" (594mm)
	1000 LB (453 KG)	23.4" (594mm)
	Square 275 LB (125 KG)	24.0" (610mm)
	Square 500 LB (227 KG)	21.0" (533mm)
	Square 900 LB (408 KG)	24.0" (610mm)
	Square 1000 LB (453 KG)	24.0" (610mm)
	Square 2000 LB (907 KG)	29.0" (737mm)
	McKAY®	less than 600 LB (272 KG)
	600 LB (272 KG)	23.4" (594mm)
	750 LB (340 KG)	23.4" (594mm)
	NATIONAL STANDARD®	400 LB (181 KG)
500 LB (227 KG)		20.4" (518mm)
900 LB (408 KG)		23.4" (594mm)
500 LB (227 KG)		20.4" (518mm)
900 LB (408 KG)		23.4" (594mm)
NOVAFIL®	550 LB (250 KG)	20.4" (518mm)
PARAMOUNT®	500 LB (227 KG)	20.4" (518mm)
	1000 LB (453 KG)	26.0" (660mm)
PITTARC® (PITINI)	250 KG (550 LB)	20.4" (518mm)
	350-450 KG (772-992 LB)	23.4" (594mm)
	600-700 KG (1323-1543 LB)	26.0" (660mm)
POLYMET®	Round Drums	23.4" (594mm)
PRAXAIR® (PROSTAR®)	Square 275 LB (125 KG)	21.0" (533mm)
	Square 550 LB (250 KG)	21.0" (533mm)
SANDVIK®	600 LB (272 KG)	20.4" (518mm)
SELECT-ARC®	250 LB (113 KG)	20.4" (518mm)
	400 LB (181 KG)	20.4" (518mm)
	500 LB (227 KG)	20.4" (518mm)
	600 LB (272 KG)	23.4" (594mm)
THERMAL ARC®	500 LB (227 KG)	20.4" (518mm)
	830 LB (376 KG)	23.4" (594mm)
TRI-MARK®	400 LB (181 KG)	20.4" (518mm)
	500 LB (227 KG)	20.4" (518mm)
	600 LB (272 KG)	23.4" (594mm)
WASHINGTON ALLOYS®	500 LB (227 KG)	20.4" (518mm)
	1000 LB (453 KG)	26.0" (660mm)
WELDMARK®	500 LB (227 KG)	20.4" (518mm)
WISCONSIN WIRE WORKS®	250 LB (113 KG)	20.4" (518mm)
	500 LB (227 KG)	20.4" (518mm)

* Drum sizes have been supplied by the manufacturer or their distributors who, at their discretion, reserve the right to change product standards without notice. To the best of ELCo's knowledge, information presented is accurate and current.

All packaging is round unless otherwise noted.